

NORMTUCKET

thickness: 0.9-1.1MM
average size: 51 sq. ft
availability: In Stock
category: Protected
finish type: Natural Smooth
raw material: South American
Made in Italy

This aniline dyed, performance leather provides abundant sophistication for all styles. The buttery soft hand coupled with natural aniline depth illuminates a timeless beauty. When wearability is a concern without compromising style and luxe, normtucket is the perfect leather.

Colorways available: Oxblood and Stone

SPECIFICATIONS

performance characteristics

PERFORMANCE LEATHER

EN ISO 4045 DETERMINE Ph & Ph (DIFFERENCE FIGURE)	Min 3,2
ISO105/B02 COLOR FASTNESS OF LEATHER TO LIGHT: XENON LAMP	Grey Scale ≥ 3 on specimen Grey Scale = 3 on Reference Blue Wool #5
ISO 11641 COLOR FASTNESS OF LEATHER TO PERSPIRATION	80 Cycles ≥ 3.5
EN ISO 11640 COLOR FASTNESS OF LEATHER TO RUBBING	500 Cycles Dry ≥ 4 250 Cycles Wet ≥ 3.5
EN ISO 11644 FINISH ADHESION	3 N/cm
EN ISO 3376 MEASURE TENSILE STRENGTH AND % ELONGATION	Tensile Strength ≥ 8 Mpa % Elongation ≤ 80%
EN ISO 5402 FLEXING ENDURANCE (FLEXOMETER METHOD)	50,000 Cycles (no finish damage cracks)
EN ISO 17233 COLD CRACK RESISTANCE OF FINISH	-15°C (no finish cracks)
EN ISO 3377-1 TEAR STRENGTH (SINGLE EDGE TEAR)	>20 N Minimum

flame resistance

CA TB 117 - 2013	Complies
NFPA - 260 CIGARETTE IGNITION	Class 1
FMVSS 302	Complies

