

# NANTUCKET

**thickness:** 0.9-1.1MM  
**average size:** 51 sq. ft  
**availability:** In Stock  
**category:** Protected  
**finish type:** Natural Smooth  
**raw material:** South American  
**Made in Italy**

The buttery soft Nantucket blends the best of both worlds leather has to offer. Although it's an aniline looking leather, Nantucket displays the natural characteristics of Italy's finest aniline leathers. In addition to the timeless look, this leather offers the highest quality protection in its class.

**Colorways available:** Chestnut, Cognac, Light Taupe, Smooth Pebble, and Stone

## SPECIFICATIONS

### performance characteristics

### PERFORMANCE LEATHER

<b>EN ISO 4045</b> DETERMINE Ph & Ph (DIFFERENCE FIGURE)	Min 3,2
<b>ISO105/B02</b> COLOR FASTNESS OF LEATHER TO LIGHT: XENON LAMP	Grey Scale ≥ 3 on specimen Grey Scale = 3 on Reference Blue Wool #5
<b>ISO 11641</b> COLOR FASTNESS OF LEATHER TO PERSPIRATION	80 Cycles ≥ 3.5
<b>EN ISO 11640</b> COLOR FASTNESS OF LEATHER TO RUBBING	500 Cycles Dry ≥ 4 250 Cycles Wet ≥ 3.5
<b>EN ISO 11644</b> FINISH ADHESION	3 N/cm
<b>EN ISO 3376</b> MEASURE TENSILE STRENGTH AND % ELONGATION	Tensile Strength ≥ 8 Mpa % Elongation ≤ 80%
<b>EN ISO 5402</b> FLEXING ENDURANCE (FLEXOMETER METHOD)	50,000 Cycles (no finish damage cracks)
<b>EN ISO 17233</b> COLD CRACK RESISTANCE OF FINISH	-15°C (no finish cracks)
<b>EN ISO 3377-1</b> TEAR STRENGTH (SINGLE EDGE TEAR)	>20 N Minimum

### flame resistance

CA TB 117 - 2013	Complies
NFPA - 260 CIGARETTE IGNITION	Class 1
FMVSS 302	Complies

